

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 6/03/2003
00000000PAGE 1
MSDS NO. 1677.2

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME
W.M. BARR & COMPANY, INC.ADDRESS
2105 Channel Avenue
Memphis, TN 38113 USAEMERGENCY TELEPHONE #1
901-775-0100EMERGENCY CONTACT
W.M. Barr Technical Services

EMERGENCY INFORMATION

"3E" 24 HOUR MEDICAL EMERGENCY #, 800 451-8346.
SEE SECTION 5 FOR ADDITIONAL EMERGENCY INFORMATIONINVENTORY ITEM #
QPT1KCHEMICAL FORMULA
1677.2PRODUCT NAME
KLEAN-STRIP PAINT THINNERREVISED BY
W.M. Barr Technical ServicesREVISION DATE
2/07/2003

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CARCINOGENICITY

SUBSTANCE DESCRIPTION	PERCENT	CAS#	NTP	ACGIH	OSHA	IARC
MINERAL SPIRITS	55- 60	N/A	N	N	N	N
** ABOVE INGREDIENT CONSISTS OF THE FOLLOWING **						
STODDARD SOLVENT, TYPE I	95-100	8052-41-3	N	N	N	N
1,2,4-TRIMETHYLBENZENE	0- 2	95-63-6	N	N	N	N
PETROLEUM DISTILLATES	40- 45	64741-85-1	N	N	N	N

SECTION 3. REGULATORY INFORMATION

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG.AGCY U/M		TWA	STEL	CEIL	SKIN	PEL
MINERAL SPIRITS	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E
EXXON RECOMMENDS AN OCCUPATIONAL EXPOSURE LIMIT OF 100 PPM TOTAL HYDROCARBON BASED ON COMPOSITION.							
STODDARD SOLVENT, TYPE I	ACGIH	PPM	100.00	N/E	N/E	N	N/E
	OSHA	PPM	100.00	N/E	N/E	N	500.00
1,2,4-TRIMETHYLBENZENE	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E
PETROLEUM DISTILLATES	ACGIH	PPM	100.00	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E

ADDITIONAL REGULATORY INFO

The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 6/03/2003
00000000PAGE 2
MSDS NO. 1677.2SECTION 3. REGULATORY INFORMATION
(CONTINUED)

CALIFORNIA (PROPOSITION #65)

Ingredients in this product are not listed on California's Prop 65 list: "Chemicals Known to the State to Cause Cancer or Reproductive Toxicity."

SEC. 313 SUPPLIER NOTIFICATION

The following information must be included in all MSDS that are copied and distributed for this material.

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40CFR 372):

SUBSTANCE DESCRIPTION	PERCENT BY WEIGHT (UPPER LIMIT)	CAS#
1,2,4-TRIMETHYLBENZENE	1	95-63-6

CLEAN AIR ACT

This formula contains no known ozone depleting chemicals.

HAZARD COMMUNICATION STANDARD

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

SECTION 4. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS

May cause dizziness, headache, watering of eyes, eye irritation, weakness, nausea, muscle twitches, and depression of central nervous system. Severe overexposure may cause convulsions, unconsciousness, and death.

SKIN CONTACT ACUTE EXPOSURE EFFECTS

None known.

EYE CONTACT ACUTE EXPOSURE EFFECTS

May cause irritation.

INGESTION ACUTE EXPOSURE EFFECTS

Harmful or fatal if swallowed. May cause nausea, weakness, muscle twitches, gastrointestinal irritation, and diarrhea. Severe overexposure may cause convulsions, unconsciousness, and death.

CHRONIC EXPOSURE EFFECTS

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause jaundice, bone marrow damage, liver damage, anemia, and skin irritation.

MEDICAL CONDITIONS AGGRAVATED

None known.

PRIMARY ROUTE OF EXPOSURE

Inhalation, ingestion, and dermal.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 6/03/2003
00000000PAGE 3
MSDS NO. 1677.2

SECTION 5. FIRST AID MEASURES

INHALATION

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT

Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

EYE CONTACT

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

INGESTION

DO NOT induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

NOTE TO PHYSICIAN

This formula is registered with POISINDEX.
Call your local poison control center for further information.

SECTION 6. FIRE FIGHTING MEASURES

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	2	1
FLAMMABILITY	2	2
REACTIVITY	0	0
OTHER	G	NA

FLASH METHOD
SETA

FLASH POINT
105.00 F 40.55 C

LOWER EXPLOSION LIMIT
1.0

GENERAL COMMENTS

OSHA FLAMMABILITY: Class II

EXTINGUISHING METHOD

Use carbon dioxide, dry powder, or foam.

FIRE FIGHTING PROCEDURES

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Stay away from heads of containers that have been exposed to intense heat or flame.

FIRE AND EXPLOSION HAZARDS

CAUTION! COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL OTHER SOURCES OF IGNITION. VAPORS MAY CAUSE FIRE. VAPORS MAY TRAVEL LONG DISTANCES TO OTHER AREAS AND ROOMS AWAY FROM WORK SITE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and until all vapors are gone from work site and all areas away from work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 6/03/2003
00000000PAGE 4
MSDS NO. 1677.2

SECTION 7. ACCIDENTAL RELEASE MEASURES

CLEAN-UP

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

WASTE DISPOSAL

Dispose in accordance with applicable local, state and federal regulations.

SECTION 8. HANDLING AND STORAGE

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

HANDLING

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

SECTION 9. TRANSPORT INFORMATION

TRANSPORTATION

For D.O.T. information, contact W.M. Barr Technical Services Department.

SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION PROTECTION

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

RESPIRATORY PROTECTION

If the work area is not well ventilated you MUST use a properly fitted and maintained NIOSH approved respirator for organic solvents. A dusk mask does not provide protection against vapors.

SKIN PROTECTION

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

EYE PROTECTION

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

OTHER PROTECTION

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 6/03/2003
00000000PAGE 5
MSDS NO. 1677.2SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION
(CONTINUED)

or shoes.

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES

VOLATILE X

100

by weight

BOILING POINT

GT 310.00 F 154.44 C BOILING RANGE: 310 F - 405 F

VAPOR DENSITY (Air = 1.0)

HEAVIER THAN AIR

EVAPORATION RATE

SLOWER THAN ETHER

BULK DENSITY

6.659

LBS/GAL AT 75 DEGREES F

pH FACTOR

N/E

PHOTOCHEMICALLY REACTIVE

YES

MAX V.O.C.

800 grams per liter (excluding exempt solvents and water)

MAX VAPOR PRESSURE

(of the V.O.C.) 3mm Hg at 20 degrees C

SECTION 12. STABILITY AND REACTIVITY

INCOMPATIBILITIES

Incompatible with strong oxidizing agents.

DECOMPOSITION

Thermal decomposition may produce carbon monoxide, and carbon dioxide.

POLYMERIZATION

Will not occur.

STABILITY

Stable.

SECTION 13. ADDITIONAL INFORMATION

IMPORTANT NOTE

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

LEGEND:

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 6/03/2003
00000000

PAGE 6
MSDS NO. 1677.2

SECTION 13. ADDITIONAL INFORMATION
(CONTINUED)

PPM = parts per million
MG/M3 = milligrams per cubic meter
N/E or NE = none established
GT = greater than
N/A or NA = not applicable
TCC = tag closed cup
TOC = tag open cup
PMCC = Pensky-Martens closed cup
IDLH = Immediately Dangerous to Life and Health

END OF MSDS