

# Material Safety Data Sheet



Zep Inc.  
1310 Seaboard Industrial Blvd.  
Atlanta, GA 30318  
1-877-I-BUY-ZEP (428-9937)  
www.zep.com

## Section 1. Chemical Product and Company Identification

**Product name** ZEPRESERVE  
**Product use** Penetrant.  
**Product code** 1434  
**Date of issue** 10/23/08 **Supersedes** 04/19/04

### Emergency Telephone Numbers

#### For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

#### For Medical Emergency

INFOTRAC: (877) 541-2016 Toll Free - All Calls  
Recorded

#### For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded  
In the District of Columbia (202) 483-7616

Printing date: 10/23/08

#### Prepared By

Compliance Services  
1420 Seaboard Industrial Blvd.  
Atlanta, GA 30318

## Section 2. Hazards Identification

### Emergency overview

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

**DANGER !**

2 2 0

COMBUSTIBLE. CAUSES EYE AND SKIN IRRITATION. HARMFUL  
IF INHALED OR ABSORBED THROUGH SKIN. HARMFUL OR  
FATAL IF SWALLOWED.

**NOTE:** MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

### Acute Effects

#### Routes of Entry

Dermal contact. Eye contact. Inhalation. Ingestion.

#### Eyes

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

#### Skin

Harmful if absorbed through the skin. Prolonged or repeated contact may dry skin and cause irritation. Skin inflammation is characterized by itching, scaling, or reddening. Defatting properties, may aggravate an existing dermatitis.

#### Inhalation

Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.

#### Ingestion

Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

### Chronic effects

Defatting to the skin. Repeated or prolonged skin contact may produce chronic inflammation or dermatitis, characterized by redness, scaling or itching. Repeated or prolonged exposure to the substance can produce damage to kidneys, liver, blood, thymus.

**Carcinogenicity** Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

**Additional Information:** See Toxicological Information (Section 11)

## Section 3. Composition/Information on Ingredients

LIGHT ALIPHATIC NAPHTHA; solvent naphtha (petroleum), medium aliphatics; formerly: light aromatic naphtha	64742-88-7	40 - 50
PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate	64742-52-5	20 - 30
HYDROTREATED LIGHT PETROLEUM DISTILLATES; paraffinic, naphthenic solvent	64742-47-8	10 - 20
DIETHYLENE GLYCOL MONOBUTYL ETHER; 2-(2-butoxyethoxy)-ethanol; butyl carbitol	112-34-5	<10
2-ETHYL HEXYL ALCOHOL; 2-ethyl-1-hexanol; 2-ethylhexanol	104-76-7	<10

## Section 4. First Aid Measures

### Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention immediately.

### Skin Contact

Wash affected area with soap or mild detergent and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.

### Inhalation

Move exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion**

Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)

**Flash Point**

Closed cup: 39.4°C (103°F)  
[Tagliabue.]

**Flammable Limits**

Not available.

**Flammability**

COMBUSTIBLE.

**Fire hazard**

Combustible liquid and vapor. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Fire-Fighting Procedures**

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam. Do not release runoff from fire to sewers or waterways. Cool closed containers exposed to fire with water.

**Section 6. Accidental Release Measures****Spill Clean up**

Eliminate all ignition sources. Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container.

**Section 7. Handling and Storage****Handling**

Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wash thoroughly after handling. Do not reuse container.

**Storage**

Eliminate all ignition sources. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

LIGHT ALIPHATIC NAPHTHA; solvent naphtha (petroleum), medium aliphatics; formerly: light aromatic naphtha

PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate

HYDROTREATED LIGHT PETROLEUM DISTILLATES; paraffinic, naphthenic solvent  
DIETHYLENE GLYCOL MONOBUTYL ETHER; 2-(2-butoxyethoxy)-ethanol; butyl carbitol

**Exposure limits**

ACGIH TLV (United States).

STEL: 200 ppm 8 hour(s).

OSHA PEL (United States).

TWA: 500 ppm 8 hour(s).

ACGIH TLV (United States).

TWA: 100 ppm 8 hour(s).

OSHA PEL (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mist

ACGIH TLV (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mist

Supplier Suggested (United States).

TWA: 100 ppm 8 hour(s).

Manufacturer (United States).

TWA: 35 ppm 8 hour(s).

**Personal Protective Equipment (PPE)****Eyes**

Safety glasses or chemical splash goggles.

**Body**

Wear appropriate protective clothing to prevent skin contact.  
Recommended: Neoprene gloves. Rubber gloves. Nitrile gloves.

**Respiratory**

Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

**Section 9. Physical and Chemical Properties****Physical State**

Liquid.

**pH**

Not applicable

**Boiling Point**

151.7°C (305°F)

**Specific Gravity**

0.81

**Solubility**

Insoluble in the following materials: cold water and hot water.

**Color** Clear. Dark Brown.

**Odor** Petroleum-like.

**Vapor Pressure** Not determined.

**Vapor Density** >1 [Air = 1]

**Evaporation Rate** 0.1 (Toluene = 1)

**VOC (Consumer)** 49.4% 3.33 (lb/gal) 399 (g/l).

**Section 10. Stability and Reactivity****Stability and Reactivity**

The product is stable.

**Incompatibility**

Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous Polymerization**

Will not occur.

**Hazardous Decomposition Products** carbon oxides (CO, CO<sub>2</sub>), sulfur oxides (SO<sub>2</sub>, SO<sub>3</sub> etc.)**Section 11. Toxicological Information****Acute Toxicity****Product/ingredient name****Result****Species****Dose****Exposure**

Hydrotreated Light Petroleum Distillates

LD50 Dermal

Rabbit

&gt;2000 mg/kg

-

LD50 Oral

Rat

&gt;5000 mg/kg

-

Diethylene Glycol Monobutyl Ether

LD50 Dermal

Rabbit

2700 mg/kg

-

LD50 Oral

Rat

5660 mg/kg

-

LD50 Oral

Mouse

2400 mg/kg

-

2-Ethylhexanol

LD50 Dermal

Rabbit

1970 mg/kg

-

LD50 Oral

Rat

2040 mg/kg

-

**Section 12. Ecological Information****Environmental Effects**

No known significant effects or critical hazards.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Code: - D001

Classification: - [Ignitable hazardous waste.]

**Section 14. Transport Information****Regulatory information****UN number****Proper shipping name****Classes****PG\*****Label****DOT Classification**

Not regulated.

Not a DOT controlled material (United States).

**IMDG Class**

Not determined.

**NOTE:** DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

**Product name**

Diethylene Glycol Monobutyl Ether (Glycol Ethers)

**Clean Water Act (CWA) 307:** No products were found.**Clean Water Act (CWA) 311:** No products were found.**Clean Air Act (CAA) 112 regulated toxic substances:** Diethylene Glycol Monobutyl Ether

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations****California Prop 65**

No products were found.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

*\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.*