TRU-TEST MANUFACTURING CO -- 015 TRU-TEST SUPREME WOODSMAN SANDING SEALER -- 8010-00F021258

======== Product Identification ===========

Product ID:015 TRU-TEST SUPREME WOODSMAN SANDING SEALER MSDS Date: 07/25/1990 FSC:8010 NIIN:00F021258 MSDS Number: BMLKK === Responsible Party === Company Name: TRU-TEST MANUFACTURING CO Address:201 JANDUS RD City:CARY State: IL ZIP:60013 Info Phone Num: (708) 639-5383 Emergency Phone Num: (800) 228-5635 CAGE: TRUTE === Contractor Identification === Company Name: TRU-TEST MANUFACTURING CO Address:201 JANDUS RD Box:City:CARY State: IL ZIP:60013 Country: US Phone: 708-639-5383 CAGE: TRUTE ====== Composition/Information on Ingredients ======== Ingred Name: KEROSENE (PETROLEUM), HYDROTREATED; PETROLEUM DISTILLATE, HYDROTREATED CAS:64742-47-8 RTECS #: OA5504000 Fraction by Wt: 30-35% OSHA PEL:500 PPM ACGIH TLV:100 PPM Ingred Name:V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS CAS:8032-32-4 RTECS #:016180000 Fraction by Wt: 30-35% Other REC Limits: STEL 400 PPM OSHA PEL: 300 PPM ACGIH TLV:300 PPM Ingred Name: ZINC STEARATE, STEARIC ACID ZINC SALT, OCTADECANOIC ACID ZINC SALT CAS:557-05-1 RTECS #:ZH5200000 Fraction by Wt: 1-5% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOL ORGANIC CMPD: <550 GM/L</pre>

RTECS #:9999999VO

Ingred Name:WEIGHT PER GALLON IN POUNDS: 7 RTECS #:9999999WG ======= Hazards Identification =========== Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES: IRRITATION. SKIN: DRYNESS. INHALATION: HEADACHE, DIZZINESS, & NAUSEA. Explanation of Carcinogenicity:NONE Effects of Overexposure: EYES: IRRITATION. SKIN: DRYNESS. INHALATION: HEADACHE, DIZZINESS, & NAUSEA. ======= First Aid Measures ============ First Aid: EYES: FLUSH W/FRESH WATER. SKIN: WASH W/WARM WATER & SOAP. INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF BREATHING STOPS. INGESTION: DON'T INDUCE VOMITING. KEEP WARM & QUIET. OBTAIN MEDICAL ATTENTION IN ALL CASES. ======== Fire Fighting Measures =========== Flash Point:105F Lower Limits: 0.9% Extinguishing Media: FOAM, CO2, DRY CHEMICAL, OR WATER FOG Fire Fighting Procedures: TREAT AS A VOLATILE LIQUID FIRE. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERED. Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. COMBUSTIBLE LIQUID. ======== Accidental Release Measures ============= Spill Release Procedures: ELMINATE IGNITION SOURCES. CONTAIN SPILL, ABSORB LIQUID W/CLAY, SAND OR FLOOR ABSORBENT. PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Handling and Storage Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF MORE THAN 2-3 INCHES WHEN POURING. Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IF >TLV. APPROVED MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING APPLICATION. Ventilation: MECHANICAL/GENERAL OR LOCAL EXHAUST TO KEEP AIR Evaporation Rate & Reference: SLOWER THAN ETHER Appearance and Odor:CLEAR Percent Volatiles by Volume: 72% ======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS

======= Disposal Considerations ===========

Waste Disposal Methods: CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. COMBUSTIBLE LIQUID.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.