

HMIS RATING	
Health	1
Flammability	4
Reactivity	3

### MATERIAL SAFETY DATA SHEET

KIMBALL-MIDWEST  
P.O. BOX 2470  
COLUMBUS, OH 43216-2470  
CORPORATE TELEPHONE: 614-219-6100  
EMERGENCY TELEPHONE: 800-424-9300

NFPA 704 RATING	
Health	1
Flammability	4
Reactivity	3
NFPA 30B LEVEL	
3	

## 1. PRODUCT IDENTIFICATION

PART NUMBER.....80-881  
PRODUCT NAME ..... ULTRA PRO• MAX GLOSS BLACK PAINT  
16OZ AEROSOL CAN  
CHEMICAL FAMILY.....N/A  
DOT SHIPPING..... Consumer Commodity ORM-D

## 2. HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	ACGIH TLV	REL	%
Acetone (00067-64-1)	-	-	-	22.56
Propane (00074-98-6)	1000ppm	1000ppm	2500ppm	15.74
N-Butane (00106-97-8)	-	800ppm	800ppm	9.24
Barium Sulfate (07727-43-7)	5mg/m3	5mg/m3	10mg/m3	8.51
*Glycol Ether EP (02807-30-9)	-	-	-	5.45
*Methyl Iso-butyl Ketone (00108-10-1)	100ppm	75ppm	75ppm	5.16
Methyl Propyl Ketone (00107-87-9)	200ppm	150ppm	250ppm	3.33
*Xylene (01330-20-7)	100ppm	150ppm	150ppm	2.69
PM Acetate (108-65-6)	-	-	-	1.83
Isobutyl Acetate (110-19-00)	150ppm	150ppm	150ppm	1.41

All chemical compounds marked with an asterisk (\*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement. \*\*Ceiling

## 3. PHYSICAL DATA

BOILING POINT (RANGE).....-44°C (-47°F)  
VAPOR PRESSURE PSIG @ 70°F..... 40 PSI, 2750 hPa  
VAPOR DENSITY (AIR = 1) ..... N/A  
SOLUBILITY IN WATER..... Slight  
SPECIFIC GRAVITY (H<sub>2</sub>O = 1)..... 0.77- 0.85  
MELTING/FREEZING POINT..... N/A  
EVAPORATION RATE (Ether=1)..... >1  
VOC content (by weight) ..... 46.1%, 495.5g/L  
APPEARANCE AND ODOR..... Black liquid/Aromatic

## 4. FIRE AND EXPLOSION DATA

FLASH POINT .....-19°C (-2°F)  
UPPER EXPLOSIVE LIMIT (%) ..... 10.9%  
LOWER EXPLOSIVE LIMIT (%) ..... 1.7%  
EXTINGUISHING MEDIA..... Extinguishing powder, CO<sub>2</sub>,  
Sand. Fight larger fires with  
water spray or alcohol resisant  
foam.

SPECIAL FIREFIGHTING PROCEDURES..... Containers can build up pressure  
if exposed to heat (fire). As in any fire, wear self-  
contained breathing apparatus pressure-demand  
(MSHA/NIOSH approved or equivalent) and full  
protective gear.

FIRE AND EXPLOSION HAZARDS..... Vapors may form explosive  
mixture with air.

NFPA Flammability Hazard.....4

## 5. HEALTH EFFECTS DATA

### SHORT TERM EFFECTS OF EXPOSURE

ROUTE OF ENTRY.....Skin absorption, Inhalation, Ingestion, Eye contact,  
Skin contact

### HEALTH HAZARDS

(ACUTE AND CHRONIC).....Extremely flammable. Irritating to eyes. Vapors  
may cause drowsiness and dizziness. May cause  
permanent brain and nervous system damage.  
Repeated overexposure can also damage kidneys,  
lungs, liver, heart and blood. Intentional misuse by  
deliberately inhaling the contents may be harmful or  
fatal.

### MEDICAL CONDITIONS GENERALLY

AGGRAVATED BY EXPOSURE.....Heart disease, respiratory  
disorders.

## 5. HEALTH EFFECTS DATA CON'T

### FIRST AID PROCEDURES

EYE CONTACT .....Immediately flush eyes with plenty of water. Get  
medical attention, if irritation persists.  
SKIN CONTACT .....Wash with soap and water. Get medical attention if  
irritation develops or persists.  
INGESTION.....If swallowed, do NOT induce vomiting. Give victim  
a glass of water or milk. Call a physician or poison  
control center immediately. Never give anything by  
mouth to an unconscious person.  
INHALATION .....Remove to fresh air. If not breathing, give artificial  
respiration. If breathing is difficult, give oxygen.  
Rescuers should put on appropriate protective  
gear. Keep victim warm. Get immediate medical  
attention.

### SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines).....Prop 65: This product contains  
chemicals known to the state of California to  
cause cancer.

## 6. REACTIVITY

STABILITY.....Stable under normal  
conditions.  
INCOMPATIBILITIES.....No dangerous reactions  
known.  
HAZARDOUS DECOMPOSITION .....No decomposition if used  
according to specifications.  
PRODUCTS .....Fumes may contain CO<sub>2</sub>, CO.  
HAZARDOUS POLYMERIZATION.....Will not occur under normal  
conditions.  
HAZARDOUS POLYMERIZATION CONDITIONS.....None known

## 7. PRECAUTIONS FOR SAFE HANDLING & USE

### PROTECTIVE EQUIPMENT

REQUIREMENTS.....Safety goggles. Local exhaust ventilation may be  
necessary to control contaminants to within TLVs  
during the use of this product.

WASH REQUIREMENTS.....Wash with soap and water.

SPILL OR LEAK PROCEDURES .....Absorb spill with inert material (e.g. dry sand  
or earth), then place in chemical waste container.

WASTE DISPOSAL METHODS .....Dispose of in accordance with local, state,  
and federal regulations

HANDLING & STORAGE .....Wash thoroughly after handling. Keep away from  
heat, sparks and flames. Store below 120°F.

OTHER PRECAUTIONS.....Use NIOSH approved respirator with an organic  
vapor cartridge; avoid prolonged breathing of  
vapors, protection provided by air purifying  
respirators is limited.

## 8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat  
or smoke while using. Wash hands after use. Use positive pressure air supplied  
respirator if there is potential for uncontrolled release, if exposure levels are  
unknown, or in any circumstance where air purifying respirators may not provide  
adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN  
APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH  
OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH  
AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED  
TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS  
THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT  
TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS  
AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR  
PURPOSES.

**KIMBALL  
MIDWEST**  
*Specializing in Materials Management since 1923*